

PRODUCT DATA

Pura[®] Insulation Remover

Pura[®] Insulation Remover is a powerful stripping agent that attacks insulation foam. Pura[®] Insulation Remover is the most effective, easy-to-handle foam urethane resin remover available.

Typical Properties

•• •	
Density, lbs/gal; kg/l	8.60; 1.03
Flash Point, ºF/ºC	204/94
Auto Ignition Temperature, °F/°C	655/346
Compatibility	Completely miscible with water and most organic solvents including chlorinated hydrocarbons
Storage	24 months

Storage

Store Pura[®] Insulation Remover in a cool, dry area.

Handling

We believe Pura[®] Insulation Remover has a low degree of hazard when used as intended. For more information, request a copy of Chem-Trend's Material Safety Data Sheet.

Packaging

Pura[®] Insulation Remover is available in 5-gallon (20-liter) and 55-gallon (208-liter) containers.

Application

Pura[®] Insulation Remover effectively removes urethane resins from metal equipment surfaces. Simply brush Pura[®] Insulation Remover onto the equipment, or surface to be cleaned, and wipe away the foam deposit.

Soaking is an effective method for heavy buildup removal. Apply generous amounts of Pura[®] Insulation Remover on the surface and allow it to sit overnight at room temperature. Additional time or application may be necessary depending upon severity of buildup. Brushing areas of the equipment, which are not amenable to soaking with Pura[®] Insulation Remover, has also been found to be effective.

Pura[®] Insulation Remover is recommended for bare metal surfaces. Do not use Pura[®] Insulation Remover for cleaning polymeric (plastic) or painted surfaces unless the surface has been carefully checked for resistance. Pura[®] Insulation Remover will also strip clear coat and/or painted finishes. While the technical information and suggestions for use contained herein are believed to be accurate and reliable, nothing stated in this bulletin is to be taken as a warranty either expressed or implied.

Further Information

Request information on our complete range of materials: custom-formulated release agents for polyurethane molding; tire lubes and bladder coatings; Mono-Coat[®] semi-permanent release coatings; aerosol formulations; mold cleaners and sealers; specialized coatings and application equipment.